


# RF292A2JCCAL Datasheet

## Product Name // 2.92mm Jack Straight 2 Hole Flange RF Connector

[View Product Page](#)


### // Product Description:

- ⊞ 2.92mm Jack Straight 2 Hole Flange RF Connector
- ⊞ Maximum Voltage: 250V
- ⊞ Temperature range: -40Å°C to +85Å°C
- ⊞ Frequency range: 0GHz - 40GHz
- ⊞ VSWR:
- ⊞ Dielectric withstanding Voltage: >750V
- ⊞ Impedance: 50Ohm
- ⊞ Body Material: Stainless Steel Passivation
- ⊞ Contact Material: Beryllium Copper

### // General Information:

Product Display Title:	2.92mm Series Pin without Extended PTFE 2 Hole Flange
Product Family:	Radio Frequency Connectors
Product Series:	2.92mm Series
Weight:	1
Body Length:	9.50mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>20N
Contact Pin Material:	Beryllium Copper
Min Coupling Torque:	0.80Nm
Max Coupling Torque:	1.10Nm
Dielectric Withstanding Voltage:	>750V
Durability:	>500 cycles
Flange Mount Length:	12.70mm
Function:	Female Flange Mount RF Connector
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	ULTEM 1000
Max Operating Temperature:	+85°C
Min Operating Temperature:	-40°C
Mount Hole Distance:	8.60mm
Min Operating Frequency:	0GHz
Max Operating Frequency:	40GHz
Pin Diameter:	0.30mm
Pin Length:	7.00mm
Thread Size:	1/4 36UNS 2A
Voltage Max:	250V
Vswr:	<1.25

#### // Product PDF Links

[2.92mm Series Product Datasheet](#)

#### // Product 3D CAD Model Links

[RF292A2JCCAL3D CAD Model](#)