



Product catalog

FCI Basics+

About FCI

Latest News

Employment



Interactive product catalog

RM/RC Solid Machined Size 16 Socket Contact for Trim Trio™

SEARCH BY :

→ Part number


 GO

- Product type
- Application
- Industry standard
- Product tradename
- Cross reference
- Alphabetic list
- Application tooling
- Fiber optics
- Systems & Assemblies
- Custom products
- Product literature
- Technical library

RC16M23K



Trim Trio™ Machined Contacts

**Region**

Asia/Pacific

Europe

Contact Type

Machined

Gender

Socket

Wire Size

16

Insulation Grip

no

Selected Features**Contact Material**

High conductive copper alloy

Spring Material

Beryllium copper

Contact Plating

0.40 µm (16 µin.) gold over nickel

Current Rating

13 A

Contact Resistance

< 3 milli ohms

Contact Retention

110 N min.

Operating Voltage

750 V RMS

Other Properties

Ordering data shown is for our standard product offering. For non-standard or custom product contact your authorized FCI representative.

[Back](#)

t



Product catalog

FCI Basics+

About FCI

Latest News

Employment



Interactive product catalog


RM/RC Solid Machined Size 16 Pin Contact for Trim Trio™

SEARCH BY :

→ Part number

 GO

- Product type
- Application
- Industry standard
- Product tradename
- Cross reference
- Alphabetic list
- Application tooling
- Fiber optics
- Systems & Assemblies
- Custom products
- Product literature
- Technical library

RM16M23K**Trim Trio™ Machined Contacts****Region****Contact Type****Gender****Wire Size****Insulation Grip****Selected Features**

Asia/Pacific

Europe

Machined

Pin

16

no

Other Properties**Contact Material**

High conductive copper alloy

Spring Material

Beryllium copper

Contact Plating

0.40 µm (16 µin.) gold over nickel

Current Rating

13 A

Contact Resistance

< 3 milli ohms

Contact Retention

110 N min.

Operating Voltage

750 V RMS

Ordering data shown is for our standard product offering. For non-standard or custom pr
contact your authorized FCI representative.

[Back](#)

t