

Applications with other ABB products

Pro M Miniature circuit breakers

smisline



S271-K10, 1 pole



S272-K10, 2 pole



S273-K10, 3 pole

For more information on Pro M miniature circuit breakers see Section 14.

Rated current (A)	1-Pole		2-Pole		3-pole	
	Catalog number	List price	Catalog number	List price	Catalog number	List price

K — 8 - 12 times magnetic trip threshold (S270)

0.5	S271-K0.5	\$ 42	S272-K0.5	\$ 96	S273-K0.5	\$ 138
1	S271-K1	42	S272-K1	96	S273-K1	138
1.6	S271-K1.6	42	S272-K1.6	96	S273-K1.6	138
2	S271-K2	42	S272-K2	96	S273-K2	138
3	S271-K3	42	S272-K3	96	S273-K3	138
4	S271-K4	42	S272-K4	96	S273-K4	138
5	S271-KS5 ①	42	S272-KS5 ①	96	S273-KS5 ①	138
6	S271-K6	42	S272-K6	96	S273-K6	138
8	S271-K8	42	S272-K8	96	S273-K8	138
10	S271-K10	42	S272-K10	96	S273-K10	138
13	S271-K13	42	S272-K13	96	S273-K13	138
15	S271-KS15 ①	42	S272-KS15 ①	96	S273-KS15 ①	138
16	S271-K16	42	S272-K16	96	S273-K16	138
20	S271-K20	42	S272-K20	96	S273-K20	138
25	S271-K25	46	S272-K25	106	S273-K25	156
30	S271-KS30 ①	48	S272-KS30 ①	106	S273-KS30 ①	158
32	S271-K32	48	S272-K32	106	S273-K32	158
40	S271-K40	52	S272-K40	116	S273-K40	174
50	S271-K50	60	S272-K50	136	S273-K50	200
60	S271-KS60 ①	68	S272-KS60 ①	152	S273-KS60 ①	228
63	S271-K63	68	S272-K63	152	S273-K63	228

B — 3 - 5 times magnetic trip threshold (S260)

6	S261-B6	\$ 36	S262-B6	\$ 78	S263-B6	\$ 118
10	S261-B10	36	S262-B10	78	S263-B10	118
13	S261-B13	36	S262-B13	78	S263-B13	118
16	S261-B16	36	S262-B16	78	S263-B16	118
20	S261-B20	38	S262-B20	86	S263-B20	130
25	S261-B25	38	S262-B25	88	S263-B25	132
32	S261-B32	40	S262-B32	94	S263-B32	142
40	S261-B40	42	S262-B40	98	S263-B40	148
50	S261-B50	48	S262-B50	112	S263-B50	170
63	S261-B63	56	S262-B63	128	S263-B63	194

C — 5 - 10 times magnetic trip threshold (S260)

0.5	S261-C0.5	\$ 42	S262-C0.5	\$ 96	S263-C0.5	\$ 138
1	S261-C1	42	S262-C1	96	S263-C1	138
1.6	S261-C1.6	42	S262-C1.6	96	S263-C1.6	138
2	S261-C2	42	S262-C2	96	S263-C2	138
3	S261-C3	42	S262-C3	96	S263-C3	138
4	S261-C4	42	S262-C4	96	S263-C4	138
6	S261-C6	42	S262-C6	96	S263-C6	138
8	S261-C8	42	S262-C8	96	S263-C8	138
10	S261-C10	42	S262-C10	96	S263-C10	138
13	S261-C13	42	S262-C13	96	S263-C13	138
16	S261-C16	42	S262-C16	96	S263-C16	138
20	S261-C20	42	S262-C20	96	S263-C20	138
25	S261-C25	46	S262-C25	106	S263-C25	156
32	S261-C32	48	S262-C32	106	S263-C32	158
40	S261-C40	52	S262-C40	116	S263-C40	174
50	S261-C50	60	S262-C50	136	S263-C50	200
63	S261-C63	68	S262-C63	152	S263-C63	228

① KS is for standard U.S. size.