

Product availability: Stock - Normally stocked in distribution facility



Main

Product	Surge protection device
Range	Square D
Device Short Name	HEPD80

Complementary

Surge Current	80 kA per phase
Voltage Rating	120/240 V AC
Number of Phases	1 phase
Wiring Configuration	3-wire
Nominal Discharge Current	10 kA
Max Number of Poles	1
SCCR	25 kA
Local Signalling	Status LED green normal operation
Height	296.93 mm (11.69 in)
Width	136.91 mm (5.39 in)
Depth	74.17 mm (2.92 in)

Environment

Enclosure Rating	NEMA 1
Enclosure Material	metal
Standards	UL 1449:ed. 4 type II NEC 285 CSA C22.2 No 8
Ambient Operating	149 °F (65 °C)

Ordering and shipping details

Category	08461 - SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	00785901980582
Package weight(Lbs)	3.32 kg (7.33 lb(US))
Returnability	Yes
Country of origin	US

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals which are known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Under investigation