



Braided Expandable Sleeving

SE200N-Q

Braided Expandable Sleeving for Heavy Duty Applications, 2 Inches (50.8 mm) Nominal Inside Diameter, 1.75" (44.5 mm) to 2.5" (63.5 mm) Bundle Diameter, Nylon 6/6, 25 Feet (7.6 Meters) Reel. Sleeving provides continuous abrasion resistance for wires, cables and tubing. The highly flexible open weave will not trap heat or humidity. Lightweight durable protection for high abrasion applications. Allows for use with irregular shapes.

Especificaciones

Material	Nylon 6.6
Color	Black
Propiedades de resistencia	Abrasion-Resistant
Temperatura máxima de funcionamiento (°C)	65
Temperatura mínima de funcionamiento (°C)	-40
Temperatura máxima de funcionamiento (°F)	149
Temperatura mínima de funcionamiento (°F)	-40
Diámetro nominal (in)	2
Diámetro nominal (mm)	50.8
Tipo de producto	Braided Expandable Sleeving
Diámetro máximo de mazo (in)	2.5
Diámetro máximo de mazo (mm)	63.5
Diámetro mínimo de mazo (in)	1.75
Diámetro mínimo de mazo (mm)	44.5

Detalles del empaque

UPC	61305682578
Cant. Pq. Est.	1
Volumen Pq. Est. (cf)	0.1606
Cant. Ct. Est.	4
Volumen Pq. Est. (cf)	0.6425