



## Pan-Wrap™ SE200TC-L Braided Expandable Sleeving

SE200TC-L

Tinned Copper Braided Sleeving, 2 Inches (50.8 mm) Nominal Inside Diameter, Current Capacity is 25 AMPS, Conforms to MIL-SPEC-AA-59569, 50 Feet (15.2 Meters) Reel. Sleeving is made from Electro-plated Tin Copper and provides EMI, RFI, and ESD Protection for cables. The sleeving provides continuous abrasion resistance for wires, cables and tubing.

### Specifications

Application	Protect Cables from Abrasion
Note	Provides EMI, RFI, and ESD Protection
Sub Brand	Pan-Wrap™
Material	Tinned Copper
Color	Silver
Resistance Properties	Abrasion-Resistant
Standards Met	CID A-A-59569 (formerly MIL SPEC QQB-575)
Maximum Operating Temperature (°C)	232
Maximum Operating Temperature (°F)	450
Nominal Diameter (In.)	2
Nominal Diameter (mm)	50.8
Overall Length (ft.)	50
Overall Length (m)	15.2
Product Type	Tinned Copper Braided Sleeving

### Packaging Detail

UPC	61305682478
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.3212
Std. Ctn. Qty.	2
Std. Ctn. Volume (cf)	0.6425