



Pan-Wrap™ SE38N-C Braided Expandable Sleeving

SE38N-C

Braided Expandable Sleeving for Heavy Duty Applications, 0.38 Inches (9.5 mm) Nominal Inside Diameter, 0.25" (mm) to 0.50" (12.7 mm) Bundle Diameter, Nylon 6/6, 100 Feet (30.5 Meters) Reel. Sleeving provides continuous abrasion resistance for wires, cables and tubing. The highly flexible open weave will not trap heat or humidity. Lightweight durable protection for high abrasion applications. Allows for use with irregular shapes.

Specifications

Material	Nylon 6.6
Color	Black
Resistance Properties	Abrasion-Resistant
Maximum Operating Temperature (°C)	65
Minimum Operating Temperature (°C)	-40
Maximum Operating Temperature (°F)	149
Minimum Operating Temperature (°F)	-40
Nominal Diameter (In.)	0.38
Nominal Diameter (mm)	9.5
Overall Length (ft.)	100
Overall Length (m)	30.5
Product Type	Braided Expandable Sleeving
Maximum Bundle Diameter (In.)	0.5
Maximum Bundle Diameter (mm)	12.7
Minimum Bundle Diameter (In.)	0.25
Minimum Bundle Diameter (mm)	6.4

Packaging Detail

UPC	61305682547
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0779
Std. Ctn. Qty.	4
Std. Ctn. Volume (cf)	0.3115