



Pan-Wrap™ SE38TC-C Braided Expandable Sleeving

SE38TC-C

Tinned Copper Braided Sleeving, 0.375 Inches (9.53 mm) Nominal Inside Diameter, Current Capacity is 25 AMPS, Conforms to MIL-SPEC-AA-59569, 100 Feet (30.5 Meters) Reel. Sleeving is made from Electro-plated Tin Copper and provides EMI, RFI, and ESD Protection for cables. The sleeving provides continuous abrasion resistance for wires, cables and tubing.

Specifications

Application	Protect Cables from Abrasion
Note	Provides EMI, RFI, and ESD Protection
Sub Brand	Pan-Wrap™
Material	Tinned Copper
Color	Silver
Resistance Properties	Abrasion-Resistant
Standards Met	CID A-A-59569 (formerly MIL SPEC QQB-575)
Maximum Operating Temperature (°C)	232
Maximum Operating Temperature (°F)	450
Nominal Diameter (In.)	0.375
Nominal Diameter (mm)	9.53
Overall Length (ft.)	100
Overall Length (m)	30.5
Product Type	Tinned Copper Braided Sleeving

Packaging Detail

UPC	61305682472
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.0779
Std. Ctn. Qty.	4
Std. Ctn. Volume (cf)	0.3115