



Pan-Wrap™ SE50TC-L Braided Expandable Sleeving

SE50TC-L

Tinned Copper Braided Sleeving, 0.5 Inches (12.7 mm) Nominal Inside Diameter, Current Capacity is 25 AMPS, Conforms to MIL-SPEC-AA-59569, 100 Feet (30.5 Meters) Reel. Sleeving is made from Electro-plated Tin Copper and provides EMI, RFI, and ESD Protection for cables. The sleeving provides continuous abrasion resistance for wires, cables and tubing.

Specifications

| | |
|------------------------------------|---|
| Application | Protect Cables from Abrasion |
| Note | Provides EMI, RFI, and ESD Protection |
| Sub Brand | Pan-Wrap™ |
| Material | Tinned Copper |
| Color | Silver |
| Resistance Properties | Abrasion-Resistant |
| Standards Met | CID A-A-59569 (formerly MIL SPEC QQB-575) |
| Maximum Operating Temperature (°C) | 232 |
| Maximum Operating Temperature (°F) | 450 |
| Nominal Diameter (In.) | 0.5 |
| Nominal Diameter (mm) | 12.7 |
| Overall Length (ft.) | 50 |
| Overall Length (m) | 15.2 |
| Product Type | Tinned Copper Braided Sleeving |

Packaging Detail

| | |
|-----------------------|-------------|
| UPC | 61305682474 |
| Std. Pkg. Qty. | 1 |
| Std. Pkg. Volume (cf) | 0.0779 |
| Std. Ctn. Qty. | 4 |
| Std. Ctn. Volume (cf) | 0.3115 |