

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_SMA-50-2-56/199_N

Rev.: B



Description

Straight cable plug

Interface Standards
IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 18 GHz

Mechanical Data

Centre contact soldered
Outer contact crimped
Weight 0.0032 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator
Coupling nut
Gasket
Crimp ferrule

Material

Copper Beryllium Alloy
Stainless Steel
Stainless Steel
PFA / PTFE
Stainless Steel
MVQ (Silicone Rubber)
Copper

Surface Plating

Gold Plating (Nickel underplated)

Passivated (Plating)

SUCOPLATE (R) Plating

Related Documents

Catalogue drawing DOU-00006102
Assembly instruction DOC-0000179078

Ordering Information

Single package 11_SMA-50-2-56/199_NE
Bulk 100 pcs package 11_SMA-50-2-56/199_NH

Additional Information

Suitable cables K_02252_D, ENVIROFLEX_316_D, G_02232_D

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions