

Rittal – The System.

Faster – better – everywhere.

► TopTherm fan-and-filter units – SK 3244.100

Date : Jun 14, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm fan-and-filter units – SK 3244.100

created: 14.06.2017 on www.rittal.com/com-en



Product description

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** IP 54
NEMA 12
With hose-proof hood: IP 56
With hose-proof hood: NEMA 3
With hose-proof hood: NEMA 3R
With hose-proof hood: NEMA 4
With hose-proof hood: NEMA 4X
With fine filter mat or hose-proof hood: IP 55
With fine filter mat or hose-proof hood: NEMA 12

Supply includes: Complete unit ready to install, including filter mat

Note: With the fan-and-filter unit 3237.XXX, electrical connection is made via two single wires on the unit; for all other fan-and-filter units, a screwless spring terminal is used.

Product features

**Air throughput
(unimpeded air flow):** At 50 Hz: 700 m³/h
At 60 Hz: 770 m³/h

**Air throughput with
outlet filter including
standard filter mat:** Number of outlet filters: 1
Number of outlet filters: 2
Model No. of outlet filter: SK 3243.200
Model No. of outlet filter: SK 3243.200
At 50 Hz: 544 m³/h
At 50 Hz: 614 m³/h
At 60 Hz: 587 m³/h
At 60 Hz: 662 m³/h

Rated operating 230 V, 1~, 50 Hz/60 Hz

voltage:

Dimensions:	Width: 323 mm Height: 323 mm
Required mounting cut-out:	Width: 292 mm Height: 292 mm
Build depth:	25 mm
Installation depth:	130.5 mm
Temperature range:	Bearing: -30°C...+70°C Operation (environment): -30°C...+55°C
Power consumption Pel:	At 50 Hz: 95 W At 60 Hz: 135 W
Rated current (max.):	At 50 Hz: 0.43 A At 60 Hz: 0.6 A
Miniature circuit-breaker/fuse:	4 A
Noise level:	At 50 Hz: 65 dB(A) At 60 Hz: 66 dB(A)
Diagonal fan:	Diagonal, 1~ capacitor motor
Packs of:	1 pc(s).
Weight/pack:	4.3 kg
EAN:	4028177652163
Customs tariff number:	84145100
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180705
Product description	SK TopTherm fan-and-filter unit, 700/770 m ³ /h, 230 V, 1~, 50/60 Hz, WH: 323x323 mm

(long):

Approvals

Approvals:	Approval overview C-UR CSA UR UR + C-UR
-------------------	---

Certificates:	EAC
----------------------	-----

Declarations:	Declaration of conformity
----------------------	---------------------------

2017 © Rittal GmbH & Co. KG