

Surface Mount SMS69273 Antenna

North America: LTE, Cellular, PCS, AWS, MDS
Europe: GSM 900, DCS, UMTS, UMTS 2600



SURFACE MOUNT SMS69273 ANTENNA

The SMS69273 antenna, features broadband and omnidirectional gain performance. It is an excellent solution for wireless access points and cellular applications. As a surface mount antenna, it features an integrated anti-theft locking mechanism.

It is ideal for both indoor and outdoor applications due to its durable and weather-proof antenna radome design.

FEATURES & BENEFITS

- Multi-band operation
- Available in various cable and connector configurations
- Wide bandwidth and omnidirectional gain performance
- Durable and weatherized radome design
- Conformance to RoHS

APPLICATIONS

- Wireless Terminal, Point-of-Sale, Machine to Machine,
- Automatic Meter Reading and Home Security

SPECIFICATIONS

TYPICAL ELECTRICAL SPECIFICATIONS	
Frequency	698 MHz ~ 960 MHz, 1710 MHz ~ 2700 MHz
Gain	0.8 dBi @ 698 MHz~960 MHz; 0.2 dBi @ 1700 MHz~2200 MHz; 0.2dBi @ 2500 MHz~2700 MHz
Average Efficiency	64% @ 698 MHz~960 MHz, 52% @ 1700 MHz~ 2200 MHz, 45% @ 2500 MHz~ 2700 MHz
Elevation Plane 3dB Beamwidth	60° @ 698 MHz~960 MHz, 50° @ 1700 MHz~ 2200 MHz, 40° @ 2500 MHz~ 2700 MHz
VSWR	2.0:1 Maximum
Polarization	Linear, Omnidirectional Radiation Pattern
Nominal Impedance	50 Ohms
Power, max.	3 Watts
Cable	LMR-195 or Equivalent (Length = 4572 mm +/- 113 mm)
RF Connector	TNC Male
Radome	PC, UV stabilized, Black
Material Substance Compliance	RoHS
Flame Retardancy	UL-94 V0
Operating Temperature Range	-30°C to +70°C
Storage Temperature Range	-40°C to +85°C
IP Rating	IP-67
Dimensions	87 mm (height) x 200 mm (diameter)
Antenna Weight	0.60 kg

CABLES AND CONNECTORS

MODEL NUMBER	CABLE TYPE	CONNECTOR
SMS69273-91TNM	36" LMR195	TNC MALE

global solutions: local support™

Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +44.(0).1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com


www.lairdtech.com

Surface Mount SMS69273 Antenna


North America: LTE, Cellular, PCS, AWS, MDS

Europe: GSM 900, DCS, UMTS, UMTS 2600


TYPICAL RADIATION PATTERNS



698-960 MHz Band



1710-2200 MHz Band



2400-2700 MHz Band

ANT-DS-SMS69273 1112

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2012 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.