



## SP200-11 SYSTEM SPECIFICATIONS

### **POWER SUPPLY**

Tip→Ground Potential	< 2 mV	True RMS, 50-500 Hz
Tip→Ground Resistance	< 2 Ω	DC, unit ON
Idle Temperature Stability	± 2°F (1.1°C) in still air	
Ambient Operating Temp.	10-40°C	
Max Enclosure Temp.	65°C	
Input Voltage	115 VAC	
Input Frequency	60 Hz	
Output Power	35 W maximum at 22°C ambient temperature	
Output Frequency	470 KHz	

### **DIMENSIONS**

LxWxH	10.8 x 8.9 x 17.0 cm
Power Supply Mass	2.3 Kg
Handpiece Mass	57 g
Power Cord	183 cm 18/3 SJT
Handpiece	122 cm carbon loaded silicone
ESD Materials	10 <sup>5</sup> -10 <sup>9</sup> ohm/square as per ASTM D257

### **STANDARD COMPLIANCE**

MIL-STD-2000  
MIL-STD-1686  
MIL-STD-45743E  
WS-6536D AND E

### **AGENCY APPROVAL**

FCC APPROVAL (USA)

New power supplies, handpieces, and tip cartridges are all certified **RoHS compliant**.

If you have any questions or concerns, please contact OK International Technical Support at [Support@okinternational.com](mailto:Support@okinternational.com) or at 714-799-9910.