



DEUTSCH
INDUSTRIAL



Strike Connector

SRK02 MD* 32A 00* Receptacle

10 Keyways and Color Marking

| | |
|---|---|
| A | B |
| C | D |
| E | F |
| G | H |
| I | J |

Cable Attachment Options



Contacts 28 x size 20 (7,5A max) & 4 x size 16 (13 A max)

| Pin Size | Part No. | Wire Gauge Range | OD | Crimp DWG | Hand Crimp Tool | Production Crimp Tool |
|----------|--------------|---|-------------------------------|--------------|------------------------|-----------------------|
| 16 | 1062-14-01** | 16 & 14 AWG / 1,0 - 2,0mm ² | 0,095-0,134 2,41-3,4mm | 0425-203-000 | DTT-16-00 DTT-16-01 | DCT-1620-02-00 |
| 16 | 1062-16-01** | 18, 16 & 14 AWG / 0,75 - 2,0mm ² | 0,075-0,115 1,90-2,92mm | 0425-203-000 | DTT-16-00 DTT-16-01 | DCT-1620-02-00 |
| 16 | 1062-16-06** | 20, 18 & 16 AWG / 0,50 - 1,0mm ² | 0,055-0,083 1,40-2,10mm | 0425-203-000 | DTT-16-00 DTT-16-01 | DCT-1620-02-00 |
| 16 | 1062-16-07** | 18, 16 & 14 AWG / 0,75 - 2,0mm ² | 0,075-0,115 1,90-2,90mm | 0425-203-000 | DTT-16-00 DTT-16-01 | DCT-1620-02-00 |
| 16 | 1062-16-1222 | 16, 14 & 12 AWG / 1,0 - 2,5mm ² | 0,075 - 0,138 1,90 - 3,4mm | 0425-039-000 | DTT-16-02 | DCT-16-02-01 |
| 20 | 1062-20-01** | 20, 18 & 16 AWG / 0,5 - 1,5mm ² | 0,075-0,108 1,90-2,75mm | 0425-207-000 | DTT-20-00 | DCT-1620-02-00 |
| 20 | 1062-20-02** | 20, 18 & 16 AWG / 0,5 - 1,5mm ² | 0,050-0,085 1,3-2,15mm | 0425-207-000 | DTT-20-02 | DCT-1620-02-00 |

** See envelop drawing for plating options

Sealing Plugs: Size 20: P/N 0413-204-2005, Size 16: P/N 114017

Accessories

Backshells for corrugated conduit NW 17 & NW 22 and option for tie wrap fastening to harnesses.



SRK BS MD 90 001



SRK BS MD ST 001

Consult "How to use receptacle module 32A" documentation