

Search Results

- Evaluate
 - FAQ's
- Design a Solution
 - Part Drawings
 - PDFSta-Strap He ..
- How to Buy
 - Bill of Material
 - Favorite Products List
 - Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'SST2HH-D30'

Your search criteria matched only one product, shown below

SST2HH-D30



- For high temperature applications up to 239°F (115°C) – indoor use
- Used for normal bundling and through -panel applications
- Small head height allows more efficient use of space in compact areas
- Exclusive two-piece design offers the lowest threading force in the industry
- Average 14% lighter than one-piece cable ties
- Releasable prior to final tensioning for bundle modifications
- *Heavy head* design (sst2hh/4hh) is available for use in through -panel applications with a larger opening up to .400"

Part Number	SST2HHD30
RoHS Compliant Status	Compliant
Part Description	Cable Tie, Heavy Head, Releasable, 8.0", Light-Heavy cross section
Product Type	Cable Ties
Material	Heat Stabilized Nylon 6.6
Color	Black
CSA Certified	Yes
UL Listed (File #E56854)	No
UL Recognized (File #E56854)	Yes
Length (In.)	8.0
Length (mm)	203
Width (In.)	.300
Width (mm)	7.6
CE Compliant	No
Cross Section	Light-Heavy
Head Height (In.)	.250
Head Height (mm)	6.4
Head Width (In.)	.590
Head Width (mm)	14.9
Locking Style	Releasable
Material Flammability Rating	UL 94V-2
Max. Bundle Diameter (In.)	2.00
Max. Bundle Diameter (mm)	50
Max. Continuous Use Temperature	239°F (115°C)
Min. Loop Tensile Strength (Lbs.)	120
Min. Loop Tensile Strength (N)	534
Pricing Description	Cable Tie, Heavy Head, 2Piece, 8.0"L (203mm), Light-Hvy, Heat Stabilized, Black
Thickness (In.)	.062
Thickness (mm)	1.6
Tool	GTH, GS4H, GS4EH, PTH, STH2, ST3EH
Min. Order UOM	PC
Min. Order Qty.	500
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.