



Wire Protection & Management > Interconnect Devices > SolderSleeve Shield Terminators



Operating Temperature (Max): 150 °C

Expanded Inside Diameter (Min): 4.32 mm [.17 in]

Recovered Inside Diameter (Max): 2.16 mm [.085 in]

Pre-Installed Lead: **Yes**

Resistance Properties: **Immersion Protection**

## Features

### Product Type Features

Interconnect Device Splice Type	Shield Terminator
Temperature Indicator Type	None
Temperature Indicator	None

### Configuration Features

Pre-Installed Lead Type	AS22759/32
Pre-Installed Lead	Yes

### Body Features

Lead Color	White/Black
Lead Plating Material	Tin
Lead Stranding	Stranded

### Dimensions

Pre-Installed Lead Wire Size	.61 mm <sup>2</sup>
Shield Outside Diameter (Min)	2.15 mm[.085 in]
Compatible Jacket Diameter Range	4.3 mm[.17 in]
Product Length	16.5 mm[.65 in]
Expanded Inside Diameter (Min)	4.32 mm[.17 in]
Recovered Inside Diameter (Max)	2.16 mm[.085 in]

### Usage Conditions

--	--



Operating Temperature (Max)	150 °C
Resistance Properties	Immersion Protection
Wire Temperature (Max)	150 °C

### Industry Standards

MIL/NAS Specification (MIL-S-83519, NAS-1747)	RT-1404
Government Qualified	No

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (37% in Solder) <b>Article Safe Usage Statements:</b> Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts



TE Part # EG8162-000  
HL1920E-230V-EURO


## Customers Also Bought



TE Part #892144-000  
222K142-25/225-0



TE Part #4407170001  
TMS-SCE-3/32-2.0-4



TE Part #971078-000  
382A023-25/225-0



TE Part #ANT-W63-WRT-SMA  
Antenna Dome Wifi6/6E RG174 SMA



TE Part #302634-000  
ST18-2-55-22-90



TE Part #055124-000  
ST18-2-55-20-90




TE Part #3823063009  
44A1121-16-0/9-9



TE Part #3822543004  
44A1121-22-0/9-9



TE Part #185652-000  
ST18-3-55-22-90



TE Part #4451823005  
2524E0311-9

## Documents

### Product Drawings

[ST63-3-55-20-90](#)

English

### Product Specifications

[Product Specification](#)

English