

STBNIP2212

standard Network Interface Module STB - Ethernet - 10 Mbit/s



Main

Range of Product	Modicon STB distributed I/O solution
Product or Component Type	Standard Network Interface Module
Concept	Transparent Ready
Port Ethernet	10BASE-T
Number of segments	1 primary, maximum 6 extensions
Number of devices per segment	0...256
Transmission rate	10 Mbit/s 9842.52 ft (3000 m) with fiber optic connection 10 Mbit/s 0.00...328.08 ft (0...100 m) according to 802.3 standard 10 Mbit/s 0.00...3280.84 ft (0...1000 m) with ConneXium cabling system
Structure type	Industrial LAN

Complementary

Number of addressable I/O module	0...32 per island
Communication Service	SNMP agent Modbus TCP/IP messaging Embedded web (configuration,diagnostics and access to variable) BootP/DHCP protocol
[Us] rated supply voltage	24 V DC
Power supply type	SELV
Maximum supply current	700 A
Supply voltage limits	19.2...30 V
Input current	430 mA supply circuit
Nominal output current	0.575 A 140...158 °F (60...70 °C) 1.2 A
Output voltage	5.25 V DC +/- 0.21 %)logic bus
Marking	CE
Overvoltage category	II
Status LED	1 LED (Green) status 1 LED (Green) 10T 1 LED (Green) island state (RUN) 1 LED (Green) power supply (PWR) 1 LED (Red) module error (ERR) 1 LED (Yellow) test mode
Depth	2.76 in (70 mm)
Height	5.05 in (128.3 mm)
Width	1.59 in (40.5 mm)
Net Weight	0.29 lb(US) (0.13 kg)

Environment

Electromagnetic compatibility	Immunity to electromagnetic interference IEC 61131-2
Product Certifications	CSA UL FM Class 1 Division 2 ATEX Cat 3G C-tick
Pollution degree	2 IEC 60664-1
Operating altitude	<= 6561.68 ft (2000 m)
IP degree of protection	IP20 conforming to EN 61131-2 class 1

Ambient air temperature for operation	32...140 °F (0...60 °C) without derating) -13...158 °F (-25...70 °C) with derating factor)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Relative humidity	95 % 140 °F (60 °C) without condensation
Vibration resistance	3 gn 58...150 Hz 35 x 7.5 mm symmetrical DIN rail 5 gn 58...150 Hz 35 x 15 mm symmetrical DIN rail +/-0.35 mm 10...58 Hz
Shock resistance	30 gn 11 ms IEC 88 reference 2-27

Ordering and shipping details

Category	18215-ADVANTYS STB I/O
Discount Schedule	PC32
GTIN	3595862055116
Nbr. of units in pkg.	1
Package weight(Lbs)	6.10 oz (173.0 g)
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.98 in (2.5 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	5.12 in (13 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	30
Package 2 Weight	12.04 lb(US) (5.46 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions

