



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	CD with software Documentation CD Installation guide Smart UPS signalling RS-232 cable
--------------------	---

Physical

Maximum Depth	6.73 in (17.1 cm)
Maximum Height	5.83 in (14.8 cm)
Net Weight	28.35 lb(US) (12.86 kg)
Maximum Width	14.25 in (36.2 cm)

Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Number of input connectors	1 Hard Wire 3-wire (1PH+N+G)
Efficiency at full load	151...302 V adjustable 160...285 V
Other Input Voltages	220 V 240 V
Nominal Input Voltage	230 V

Output

Kw Rating	325 W
Max Configurable Power (Watts)	325 W
Harmonic distortion	Less than 5%
Output Frequency (sync to mains)	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
Other Output Voltages	220 V 240 V
Topology	Line Interactive
Output connector type	Hard Wire 3-wire (H N + E) 1
Output voltage	230 V

Conformance

Product certifications	CE VDE
------------------------	-----------

Environmental

Ambient air temperature for operation	32...122 °F (0...50 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	55 dBA
Online Thermal Dissipation	90 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-Acid battery
Included Battery Modules	1
Battery Slots Empty	1
Typical recharge time	2 h
RBC Quantity	1
Liquid Electrolyte Value	0

Communications & Management

Free slots	1
Control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering

Surge energy rating	540 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

Ordering and shipping details

Package weight(Lbs)	29.37 lb(US) (13.32 kg)
---------------------	-------------------------

Packing Units

Package 1 Height	11.69 in (29.7 cm)
Package 1 width	11.69 in (29.7 cm)
Package 1 Length	18.94 in (48.1 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------
