



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	CD with software Documentation CD Installation guide Smart UPS signalling RS-232 cable
--------------------	---

### Physical

Maximum Depth	6.73 in (17.1 cm)
Maximum Height	5.83 in (14.8 cm)
Net Weight	28.35 lb(US) (12.86 kg)
Maximum Width	14.25 in (36.2 cm)

### Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Number of input connectors	1 Hard Wire 3-wire (1PH+N+G)
Efficiency at full load	151...302 V adjustable 160...285 V
Other Input Voltages	220 V 240 V
Nominal Input Voltage	230 V

### Output

Kw Rating	325 W
Max Configurable Power (Watts)	325 W
Harmonic distortion	Less than 5%
Output Frequency (sync to mains)	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
Other Output Voltages	220 V 240 V
Topology	Line Interactive
Output connector type	Hard Wire 3-wire (H N + E) 1
Output voltage	230 V

## Conformance

Product certifications	CE VDE
------------------------	-----------

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	55 dBA
Online Thermal Dissipation	90 Btu/h
IP degree of protection	IP20

## Batteries & Runtime

Battery type	Lead-Acid battery
Included Battery Modules	1
Battery Slots Empty	1
Typical recharge time	2 h
RBC Quantity	1
Liquid Electrolyte Value	0

## Communications & Management

Free slots	1
Control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (EPO)	Yes

## Surge Protection and Filtering

Surge energy rating	540 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

## Ordering and shipping details

Package weight(Lbs)	29.37 lb(US) (13.32 kg)
---------------------	-------------------------

## Packing Units

Package 1 Height	11.69 in (29.7 cm)
Package 1 width	11.69 in (29.7 cm)
Package 1 Length	18.94 in (48.1 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

---

Warranty	2 years repair or replace
----------	---------------------------

---