


Capacitor, tantalum, 68 uF, 7343, +/-10% Tol, 25V@85C



Dimensions (mm)		
Symbol	Dimension	Tolerance
L	7.3	+/-0.3
W	4.3	+/-0.3
H	4	+/-0.3
F	2.4	+/-0.1
S	1.3	+/-0.3
B	0.5	+/-0.15
X	0.1	+/-0.1
P	1.7	ref
R	1	ref
T	0.13	ref
A	3.8	min
G	3.5	ref
E	3.5	ref

Notes:

-In polarity stripe, at KEMET's option, type may be indicated:
 no symbol = Standard (or low leakage) MnO2 tantalum chip, O = LowESR T494, R = Low ESR T495, F = Fused T496, HT = 150C rated T498 (or B45196P, B45198P), H = 175C rated T499, M = Multiple anode construction T510 (and B45396R), KO = Organic cathode T520 or T521, KT = High temp organic cathode T525, KM = Multiple anode organic cathode T530, FD= Organic cathode face down terminals T528.

General Information	
Manufacturer:	KEMET

Electrical Specifications	
Capacitance:	68 uF
Voltage DC @ 85C:	25V
Voltage DC @ 105C:	21V
Voltage DC @ 125C:	17V
Tolerance:	+/-10%
Application:	General Purpose / Low ESR
Temperature Range:	-55/+125C
Body Type:	Molded Chip
Construction:	Std Chip-MnO2
ESR:	125 mOhm
Footprint:	7343
Termination:	Tin
Leakage Current:	17 uA
Dissipation Factor:	8%
Ripple @ 25C:	1.149 A
Ripple @ 85C:	1.0341 A
Ripple @ 105C:	0.747 A
Ripple @ 125C:	0.4596 A

Packaging Specifications	
Package Kind:	T&R
Package Size:	13in
Package Quantity:	2000