

TFH232-22UEDR

- High level of stability
- 1 Cable entry M 20 x 1.5
- Low operating height of pedal
- Protective shield with wide opening

Data

Ordering data

Product type description	TFH 232-22UEDR
Article number (order number)	101192630
EAN (European Article Number)	4030661403533
eCl@ss number, Version 9.0	27-37-12-23

Certifications

Certificates	cULus
	CCC
	EAC

General data

Product name	TFH 232
Standards	EN 60947-5-1 DIN VDE 0660-200 BG-GS-ET-15
Enclosure material	Aluminium
Enclosure coating material	powder-coated
Material of the cover	Aluminium
Material of the pedal	Glass-fibre, reinforced thermoplastic
Material of the protective shield	Aluminium
Colour of the product	RAL 9006
Gross weight	2,180 g

General data - Features

Probing possible	Yes
------------------	-----

Latching	Yes
Suitable for EMERGENCY-OFF	Yes
Number of openers	2
Number of shutters	2

Safety appraisal

Standards	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	100,000 Operations
-----------------------------------	--------------------

Mechanical data

Mechanical life, minimum	1,000,000 Operations
--------------------------	----------------------

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable section, maximum	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Width	170 mm
Height	189 mm
Depth	274 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+85 °C
Relative humidity, minimum	30 %
Relative humidity, maximum	95 %
Note (Relative humidity)	non-condensing non-icing
Resistance to vibrations to EN 60068-2-6	10 ... 150 Hz (0.35 mm / 5 g)
Resistance to shock	30 g / 11 ms

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------


	III
Degree of pollution to VDE 0100	3

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	NO contact, NC contact
Switching principle	Creep circuit element
Switching frequency	3,600 /h

Pictures

Product picture (catalogue individual photo)




ID: ktfh-f02

| 28,2 kB | .png | 74.083 x 58.208 mm - 210 x 165
Pixel - 72 dpi

| 342,8 kB | .jpg | 352.778 x 276.578 mm - 1000 x 784
Pixel - 72 dpi

| 39,9 kB | .jpg | 27.093 x 21.251 mm - 320 x 251 Pixel
- 300 dpi

Dimensional drawing basic component



ID: 1tfh-g02


| 142,0 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691
Pixel - 72 dpi

| 11,1 kB | .png | 74.083 x 51.153 mm - 210 x 145
Pixel - 72 dpi

| 32,3 kB | .jpg | 112.889 x 77.964 mm - 320 x 221
Pixel - 72 dpi

| 42,6 kB | .cdr |

Diagram



ID: ktf--k02

| 25,3 kB | .jpg | 112.889 x 54.681 mm - 320 x 155

Pixel - 72 dpi

| 17,4 kB | .cdr |

Product in the environment (application)



ID: ktfhvf01

| 279,2 kB | .png | 50.038 x 37.592 mm - 591 x 444

Pixel - 300 dpi

| 460,9 kB | .jpg | 352.778 x 264.936 mm - 1000 x 751

Pixel - 72 dpi


| 11,8 kB | .jpg | 149.931 x 112.536 mm - 425 x 319

Pixel - 72 dpi

| 45,7 kB | .jpg | 112.889 x 84.667 mm - 320 x 240

Pixel - 72 dpi

Operating principle



ID: ktf--a01

| 36,3 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 08.07.2020 17:27:52