

Mushroom Switches — TP4 Series

- ▶ Momentary or Latching
- ▶ Sealed IP40 or IP65
- ▶ 1 NO and 1 NC Set of Contacts Per Block
- ▶ Up to 3 Contact Blocks Per Switch



30 mm Mushroom Head Cap — IP65 Rated

The TP4 Series switch fits a 22.5 mm panel cutout. **Rating:** 250 VAC, 5 A. Splashproof and oil tight to IP65 specifications.



Momentary Switch

Stock No.	Mfr.'s Type	Contact Form	Cap Color*	EACH	
				1-14	15-24
70162363	TH404119RED	SPST	Red	39.29	37.64

Maintained Switch

70162587	TH414219RED	DPDT	Red	43.17	41.75
70162366	TH414119RED	SPDT	Red	51.72	46.53

*Caps also available in white, yellow, green and blue.

24 mm Mushroom Head Cap — IP40 Rated



Momentary Switch

The TP4 Series mushroom cap switch fits a 16.2 mm panel cutout. Rated at 5 A @ 250 VAC. Red cap.*

Stock No.	Mfr.'s Type	Contact Form	EACH	
			1-14	15-24
70162630	TH404104RED	SPST	20.98	19.23

*Caps also available in white, yellow, green, blue and black.

Mushroom Cap Twist Release — TH8 Series

The TH8 Mushroom Cap Twist Release mounts in a 16.2 mm round panel cutout.

Mushroom Cap Twist Reset



Stock No.	Mfr.'s Type	Description	EACH	
			1-14	15-24
70162680	TH880003000	1 NO + 1 NC, Printing on Cap	26.98	25.05
70162682	TH880004000	2 NC, Printing on Cap	26.98	25.05

Two Position Keyswitch — TK2 Series

- ▶ Compact Format
- ▶ Gold Plated Contacts
- ▶ UL, CSA and VDE Approvals
- ▶ 2 Keys Per Switch



Maintained

The TK2 Two Position Keyswitch has two 1 NO + 1 NC contact blocks. It is a KABA micro switch. Keyswitch needs a bezel. Three position, different cylinder elements and different key removable positions available. Momentary also are available.

Stock No.	Mfr.'s Type	Key Removable Position	EACH	
			1-14	15-24
70162582	TH548036000	Position 1	36.12	32.83

Emergency Stop — TE8 Series

The TE8 Series switches have a monoblock contact block rated at 6 A @ 230 VAC. They are protected to IP66/67. CE in conformity to the European community. VDE approval is according to IEC 947-5-1.

TE8 Emergency Stop

Push/twist release or push/pull release mounts in a 16.2 mm round panel cutout.

Stock No.	Mfr.'s Type	Description	EACH	
			1-14	15-24
70162580	TH880203000	1 NO + 1 NC Rotary Reset	30.07	29.10
70162615	TH880204000	2 NC Rotary Reset	31.28	30.28
70162581	TH893002000	43 mm Yellow Plastic Disk*	2.62	2.54

*Emergency Stop printed in English, German and French on front of disk.



Rotary Reset



Plastic Disk

TE1 Emergency Stop

The TE1 Series switches are rated 2 A at 250 VAC. They are protected to IP65. Non-illuminated or illuminated (illuminated is prewired). Approvals: EN60947-1; EN 60947-5-1; EN 60947-5-5. Rotary reset mounts in 16.2 mm round panel cutout. Compact with panel depth of <20 mm.

Stock No.	Mfr.'s Type	Description	EACH	
			1-24	25+
70162460	TE180203202	1 NC + 1 NO, 30 mm cap, Illum.	30.24	28.14
70162461	TE180204202	2 NC, 30 mm cap, Illum.	25.50	23.92
70162454	TE180203101	1 NC + 1 NO; 25 mm cap, Non-illum.	18.55	17.38
70162458	TE180203102	1 NC + 1 NO; 30 mm cap, Non-illum.	20.50	18.93
70162455	TE180204101	2 NC, 25 mm cap, Non-illum.	18.55	17.38
70162459	TE180204102	2 NC, 30 mm cap, Non-illum.	20.49	18.08

*Shown with optional yellow plastic disc (43 mm dia.), to order see image and table above on this same page.



25 mm



30 mm*