

Product availability: Stock - Normally stocked in distribution facility



Main

| | |
|---------------------------------------|---|
| Range of product | Twido |
| Accessory / separate part category | Connection accessories |
| Accessory / separate part type | Tap isolation box |
| Accessory / separate part designation | Tap isolation box |
| Accessory / separate part destination | RS485 serial link |
| Product specific application | Lines prepolarised (2 R 620 Ohm) RS485 line isolation Line end adaptor (RC 120 Ohm, 1 nF) |

Complementary

| | |
|---------------------------|--|
| Range compatibility | Twido programmable controller Modicon M238 logic controller |
| [Us] rated supply voltage | 24 V |
| Supply circuit type | DC |
| Supply | External |
| Electrical connection | 1 screw terminal block 2 connectors RJ45 for tap-off) |
| Mounting support | 35 mm symmetrical DIN rail |
| Product weight | 0.22 lb(US) (0.1 kg) |

Ordering and shipping details

| | |
|---------------------|--------------------------|
| Category | 22531 - PLCS, TWIDO, TWD |
| Discount Schedule | PC12 |
| GTIN | 00785901899044 |
| Package weight(Lbs) | 0.15 kg (0.34 lb(US)) |
| Returnability | No |
| Country of origin | ID |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.