


Solenoid coil

VACN-N-K11-1-0.5-U4-M

Part number: 8029146

FESTO



Data sheet

Feature	Value
Type of actuation	electrical
Assembly position	Any
Duty cycle	100%
Insulation class	H
Enamelled wire insulation class	H
Characteristic coil data	24 V DC: 4.6 W
Permissible voltage fluctuation	+/- 10 %
Explosion ignition protection type Gas	AEx m II T4 Ex m II T4
Explosion protection certification outside the EU	Class I, Div. 1 (CA) Class I, Div. 1 (US) Class I, Div. 2 (CA) Class II, Div. 1 (CA) Class II, Div. 1 (US) Class III, Div. 1 (CA) Class III, Div. 1 (US) EPL Gb (US)
Explosion-proof ambient temperature	-20°C ≤ Ta ≤ +60°C
Certificate issuing department	CSA 265489 DNVGL-TAA000011J FM 3053936
Corrosion resistance classification CRC	2 - Moderate corrosion stress
Protection class	IP65
Ambient temperature	-20 ... 60 °C
Maritime classification	see certificate
Product weight	207 g
Electrical connection	Cable
Cable length	0.61 m
Mounting type	With knurled nut
Materials note	Contains PWIS substances Conforms to RoHS
Material housing	Plastic Steel
Material winding	Copper