

Product availability: Stock - Normally stocked in distribution facility



### Main

Range of product	Altivar
Product or component type	Digital encoder interface module
Range compatibility	Altivar Process ATV900 Altivar Process Modular Altivar Machine ATV340
Communication port protocol	RS422
Encoder type	EnDat 2.2 A/B/I incremental XCC1 type R A/B/I incremental XCC1 type X SSI absolute encoder XCC2 type SG SSI absolute encoder XCC3 type SB
[Us] rated supply voltage	5 V DC 4.75...5.25 V) 12 V DC 11.4...12.6 V) 24 V DC 22.8...25.2 V)

### Complementary

Maximum supply current	0.25 A 5 V DC 0.1 A 12 V DC 0.05 A 24 V DC
Protection type	Short-circuit protection Overload protection
Maximum cable distance between devices	328.08 Ft (100 m) A/B/I) 164.04 Ft (50 m) SSI) 328.08 Ft (100 m) SSI)at 300 kHz 164.04 Ft (50 m) EnDat 2.2) 328.08 ft (100 m) EnDat 2.2)with propagation delay compensation
Maximum operating frequency	1000 kHz
Input signal	Data+, Data- EnDat 2.2) Data+, Data- SSI) Temp+, Temp- A+,A-/B+,B-/I+,I- A/B/I) TTL
Input impedance	121 Ohm
Output signal	Clock+, Clock- SSI) Data+, Data-, Clock+, Clock- EnDat 2.2)
Connector type	1 female high density SUB-D 15
Net weight	0.33 lb(US) (0.15 kg)

### Ordering and shipping details

Category	22209 - ATV650
Discount Schedule	CP4E
GTIN	00785901094005
Package weight(Lbs)	0.15 kg (0.33 lb(US))
Returnability	Yes
Country of origin	ID

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>