



Main

Product or component type	Communication card
---------------------------	--------------------

Complementary

Range compatibility	Altivar 32 Lexium 32
Communication port protocol	DeviceNet
Electrical connection	1 connector 1 removable 5-way screw connector
Transmission rate	125 kbps, 250 kbps and 500 kbps configurable
Cable length	500 m (125 kbps) 100 m (500 kbps)
Addressing	1...63 configurable by graphic terminal/SoMove software
Communication service	Communication monitoring time out adjustable by DeviceNet configurator Auto device replacement ODVA AC drive and CiA 402 profile Outputs : polled Inputs : polled, change of state, cyclic
Display type	1 LED for NS (Network Status) 1 LED for MS (Module Status)
Diagnostic function	Control mode received by graphic terminal Received instruction by graphic terminal

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1020 - Schneider Electric declaration of conformity

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.