




3 and 5-Wire Cordsets, Reverse Key (B-Code)

- NEMA 1, 3, 4, 6P
- IEC IP68 Protection
- 250 V, 4 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
WAKW ..** 	WAKW 4T-*/S626 WWAKW 4T-*/S626	WASW 4T-*/S626 WWASW 4T-*/S626	AWM PVC Grey, 3x20 AWG, 105°C, 5.1 mm OD, Cable #RF20017-*M†, flexlife*	1. BN 2. BU 4. GN/YE
WWAKW ..** 	WAKW 4T-*/S821 WWAKW 4T-*/S821	WASW 4T-*/S821 WWASW 4T-2/S821	PVC Yellow, 3x18 AWG, 80°C, 250°C short term, 5.7 mm OD, Cable #RF04159-*M†, Weld Flash Immune, High Temp Immune	1. RD 2. RD/WH 4. GN
WASW ..** 	WAKW 4.5T-*/S101 WWAKW 4.5T-*/S101	WASW 4.5T-*/S101 WWASW 4.5T-*/S101	AWM PVC Grey, 4x22, 1x20 AWG, 105°C, 5.7 mm OD, Cable #RF50563-*M†, flexlife	1. BN 2. WH 3. BU 4. BK 5. GN/YE
WWASW ..** 	WAKW 4.5T-*/S618 WWAKW 4.5T-*/S618	WASW 4.5T-*/S618 WWASW 4.5T-*/S618	AWM TPE Grey, 5x22 AWG, 105°C, 5.7 mm OD, Cable #RF50909-*M†, Flexlife-20, High Flex - Over 20 Million Cycles	1. BN 2. WH 3. BU 4. BK 5. GY
	WAKW 4.5T-*/S653 WWAKW 4.5T-*/S653	WASW 4.5T-*/S653 WWASW 4.5T-*/S653	AWM AWM PVC Grey, 5x22 AWG, 105°C, 5.7 mm OD, Cable #RF50609-*M†, EMI/RFI Protection	
			AWM AWM PVC Grey, 4x22 AWG, 105°C, 5.1 mm OD, Cable #RF50577-*M†, EMI/RFI Protection	1. BN 2. WH 3. BU 4. BK 5. Drain



* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

** Standard coupling nut material is nickel plated brass "WAKW.."; "WAKKW.." indicates nylon and "WAKVW.." indicates stainless steel.

† See Section N for **reelfast**® cable information.