

# WSP80/WP80

Universal SMD and THT applications both small and large; lowest cost, non-cartridge style tips in entire range.

Effective heat transfer via best material silver core  
Fast ramp up and recovery  
Designed for universal applications

80W, 24V




WSP80      WSP80      Pencil, LTB tip  
WP80      T0052918099      Pencil, LTB tip  
MPR80SET      T0053313199      Pencil, LTH tip, KH25P stand

WP80SET  
WP80 pencil, LTB tip, WDH stand  
T0052918199




## CHISEL



LT	Ø a mm	b mm	c mm	Order number
LT 1SC	0.4	0.15	15.0	T0054449499
LT 1SCNW*	0.3	0.1	15.0	T0054449799
LT A	1.6	0.7	12.5	LT A
LT ASL	1.6	0.45	12.5	T0054451699
				<b>NEW</b>
LT B	2.4	0.8	12.5	LT B
LT BSL	2.4	0.45	12.5	T0054451799
				<b>NEW</b>
LT H	0.8	0.4	12.5	LT H
LT HSL	0.8	0.4	12.5	T0054451899
				<b>NEW</b>
LT C	3.2	0.8	12.5	LT C
LT D	4.6	0.8	12.5	LT D

Type	Ø a mm	b mm	c mm	Order number
LT DLL	4.6	1.2	12.5	T0054444899
LT K	1.2	0.4	20.0	LT K
LT L	2.0	1.0	20.0	LT L
LT M	3.2	1.2	20.0	LT M
LT HX 30°	0.8	0.4	17.5	LT HX
LT ALX 30°	1.6	0.7	17.5	LT ALX
LT BX 30°	2.4	0.8	17.5	T0054444299
LT AX 30°	1.6	0.8	14.1	LT AX
LT 4X 30°	1.2	0.4	17.2	LT 4X
LT MX 30°	3.2	1.2	20.0	T0054446999

## ROUND



Type	Ø a mm	c mm	Order number
LT 1S	0.2	15.0	LT 1S
LT 1SNW*	0.1	15.0	T0054449699
LT 1SA	0.5	15.0	T0054448899
LT 1	0.25	13.0	LT 1
LT 1LNW*	0.1	25.4	T0054449899

Type	Ø a mm	c mm	Order number
LT 1A	0.5	13.0	T0054448999
LT AS	1.6	12.5	LT AS
LT CS	3.2	12.5	LT CS
LT 1SLX 30°	0.4	22.0	LT 1SLX
LT 1X 30°	0.4	13.0	LT 1X

\* non-wettable

