

Square D > Online Catalog > My Product List > Product Detail

 [Add to My Product List](#)



## Product Detail

**XS1M18MA230K**  
INDUCTIVE SENSOR 240VAC 200MA XS +OPTIONS

[Product Characteristics](#) | [Digest Information](#) | [Docs & Literature](#) | [Pricing & Ordering](#)

### Product Characteristics

<b>XS1M18MA230K</b>	INDUCTIVE PROX
Body style	Tubular - 18 mm diameter
Nominal sensing distance	5 mm
Mounting configuration	Shielded
Case/enclosure material	Nickel plated brass
Output mode	NO
Circuit type	AC/DC 2 wire
Connection	Micro style connector (AC)
Nominal voltage	24-240V AC/24-210V DC
Maximum load	300 ma AC/ 200 ma DC
Operating frequency	25 Hz (AC)/ 3000 Hz (DC)
Temperature range	-25 to 70 C
Alt Freq	No
Short circuit protection	No

### From the Digest

No listing in Digest 173

### Documentation & Literature

Disclaimer: Not all of the product information below may apply to this particular part number. Please check the documentation to ensure proper application.

#### Literature

	<a href="#">Application Bulletin, Sensor Solutions, Signaling State of Valve</a>	9006HO9505
	<a href="#">Application Bulletin, Sensor Solutions, Rotation Monitoring</a>	9006HO9521
	<a href="#">Application Bulletin, Sensor Solutions, Lock Gates</a>	9006HO9514
	<a href="#">Application Bulletin, Sensor Solutions, Heating Element Position</a>	9006HO9509

### Pricing and Ordering Information

<b>Category</b>	22486 - Sensors, Proximity, XS
<b>Discount Schedule</b>	DS2
<b>Article Number</b>	785901314349
<b>Package Qty</b>	1
<b>Weight (lbs.)</b>	0.16
<b>Availability Code</b>	S
<b>Returnability</b>	Y

