



IP65 Rotary Handle Mechanism ①②③④






| | Description | Enclosure Rating | Pkg. Qty. ⑤ | Catalog Number |
|---|---|----------------------|-------------|---------------------|
| XTPAXRHM_  | Complete Kits—Includes Handle, Shaft and Required Hardware | | | |
| | Rotary handle mechanism—black ⑥ | IP65 | 1 | XTPAXRHMB |
| | Rotary handle mechanism—red/yellow ⑦ | NEMA 12 UL/CSA 4X | 1 | XTPAXRHMY |
| | Rotary handle mechanism—black—rotated 90° from vertical ⑥ | | 1 | XTPAXRHM90B |
| | Rotary handle mechanism—red/yellow—rotated 90° from vertical ⑦ | | 1 | XTPAXRHM90RY |
| XTPAXRHMSFT  | Separate Parts | | | |
| | Shaft only—includes shaft to mount to XTPR, 175 mm length | — | 10 | XTPAXRHMSFT |
| | MMP shaft support, metal, D-frame MMP only | — | 20 | XTPAXMBM |
| | Replacement lockable handle for XTPR | — | 1 | XTPAXLRH |

XTPAXSW

Sealing Facility

| Description | Pkg. Qty. ⑤ | Catalog Number |
|---|-------------|----------------|
| To prevent tampering with the overload release and the test function. It can be sealed using industry standard sealing wire. For use with XTPR manual motor protectors. | 5 | XTPAXSW |

Three-Phase Commoning Links ⑥

| For Use with... | Qty. MMP | MMP Frame Size | Pkg. Qty. ⑤ | Catalog Number | | |
|---|----------|---|--------------------|--------------------|-------------------|--------------------|
|  | 2 | B | 10 | XTPAXCLKA2 | | |
| | | D | 1 | XTPAXCLKA2D | | |
| | 3 | B | 10 | XTPAXCLKA3 | | |
| | | D | 1 | XTPAXCLKA3D | | |
| | | B | 10 | XTPAXCLKA4 | | |
|  | 4 | B | 10 | XTPAXCLKA4 | | |
| | | D | 1 | XTPAXCLKA4D | | |
| | 5 | B | 10 | XTPAXCLKA5 | | |
| | |  | 2 | B | 10 | XTPAXCLKB2 |
| | | | | D | 1 | XTPAXCLKB2D |
| 3 | B | | 10 | XTPAXCLKB3 | | |
| | D | | 1 | XTPAXCLKB3D | | |
| | 4 | | B | 10 | XTPAXCLKB4 | |
| D | | 1 | XTPAXCLKB4D | | | |
|  | 5 | B | 10 | XTPAXCLKB5 | | |
| | |  | 2 | B | 10 | XTPAXCLKC2 |
| | 4 | | | D | 1 | XTPAXCLKC4D |

For parallel power feed to several manual motor protectors on terminals 1, 3 and 5.

Notes

- ① Plug-in connection shafts, XTPAXRHMSFT_ can be cut to desired length for mounting depths of 100–240 mm. Carrier with extension shaft included.
- ② With ON/OFF switch position and "+" (tripped), lockable with 3 padlocks, 4–8 mm hasp. Can be locked in the OFF position, if required.
- ③ Rotary handle mechanisms ship with door interlock disabled. See instruction publication with product for how to enable door interlock.
- ④ Not for use with XTPAXFAEM20 early-make front-mount auxiliary contact.
- ⑤ Orders must be placed in multiples of package quantity listed.
- ⑥ For use on main switches to IEC/EN 60204.
- ⑦ For use on main switches with emergency-stop function to IEC/EN 60204.
- ⑧ Protected against accidental contact. Frame B short-circuit proof $U_b = 690V$, $I_b = 63A$. Frame B links can be combined by rotating mounting.