

# XU5M18MA230W

Photoelectric sensors XU, XU5, diffuse, 90°, Sn  
0.4 m, 24...240VAC/DC, cable 2 m



## Main

|                               |  |
|-------------------------------|--|
| Range of product              | Telemecanique Photoelectric sensors XU |
| Series name                   | General purpose single mode            |
| Electronic sensor type        | Photo-electric sensor                  |
| Sensor name                   | XU5                                    |
| Sensor design                 | Cylindrical M18                        |
| Detection system              | Diffuse                                |
| Material                      | Metal                                  |
| Line of sight type            | 90° lateral                            |
| Type of output signal         | Discrete                               |
| Supply circuit type           | AC/DC                                  |
| Wiring technique              | 2-wire                                 |
| Discrete output function      | 1 NO                                   |
| Electrical connection         | Cable                                  |
| Cable length                  | 2 m                                    |
| Product specific application  | -                                      |
| Emission                      | Infrared diffuse                       |
| [Sn] nominal sensing distance | 0.4 m diffuse                          |

## Complementary

|                           |   |
|---------------------------|---|
| Enclosure material        | Nickel plated brass   |
| Lens material             | PMMA  |
| Maximum sensing distance  | 0.6 m   |
| Output type               | Solid state   |
| Add on output             | Without   |
| Wire insulation material  | PvR   |
| Status LED                | 1 LED (yellow) for output state   |
| [Us] rated supply voltage | 24...240 V AC/DC  |
| Supply voltage limits     | 20...264 V AC/DC  |
| Maximum residual current  | 1.5 mA open state   |
| Switching capacity in mA  | 10...200 mA (to be used with 0.4 A quick-blow fuse in series with the load) |
| Switching frequency       | <= 25 Hz  |
| Maximum voltage drop      | <6 V (closed state)   |
| Maximum delay first up    | 300 ms  |
| Maximum delay response    | 20 ms   |
| Maximum delay recovery    | 20 ms   |
| Setting-up                | Sensitivity adjustment  |
| Diameter                  | 18 mm   |
| Length                    | 97 mm   |
| Net weight                | 0.15 kg   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                                       |   |
|---------------------------------------|---|
| Product certifications                | UL<br>CE<br>CSA   |
| Ambient air temperature for operation | -25...55 °C   |
| Ambient air temperature for storage   | -40...70 °C   |
| Vibration resistance                  | 7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6 |
| Shock resistance                      | 30 gn (duration = 11 ms) conforming to IEC 60068-2-27                     |
| IP degree of protection               | IP67 double insulation conforming to IEC 60529                            |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 4.2 cm   |
| Package 1 Width              | 9.6 cm   |
| Package 1 Length             | 13.2 cm  |
| Package 1 Weight             | 137.0 g  |
| Unit Type of Package 2       | S02      |
| Number of Units in Package 2 | 22       |
| Package 2 Height             | 15.0 cm  |
| Package 2 Width              | 30.0 cm  |
| Package 2 Length             | 40.0 cm  |
| Package 2 Weight             | 3.469 kg |


## Offer Sustainability

|                          |   |
|--------------------------|---|
| REACH Regulation         | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive        | Not applicable, out of EU RoHS legal scope    |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a> |
| Circularity Profile      | <a href="#">End Of Life Information</a>       |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions




---

## Wiring Schemes

---

### 2-wire AC or DC




BU : Blue  
BN : Brown

---

Detection Curves

---

Diffuse System



- 1 : White 90%
  - 2 : Grey 18%
- Object 10 x 10 cm