



BURNDY Catalog Number
UPC Number
Description
Status

YA31L2NT38
 7818100203888
 HYDENT-NARROW-2 HOLES-35
 Active

Web Use
 BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	3.51
Barrell Style	Chamfered
Bolt Hole Size (in)	0.39
Barrel Type	Standard
Thickness	0.18
B Length (in)	1.06
Pad Width (in)	0.96
E - in	1.00
Strip Length	1-1/8
General	
Number of Holes	2
Product Description	Flex Conductor Standard Barrel Narrow, 350 kcmil, 3/8 in, 3.51 in L
Conductor(s)	
Flex (Class G) Size - Range	N/A
Flex (Class H) Size - Range	N/A
Flex (Class I) Size - Range	N/A
Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	350 kcmil
Physical	
Type of Plating	Tin - Electro Plated
Color Code	Red
Plated (Yes or No)	Y
Index Number	18
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175