



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA31LB  
 7818105049633  
 BELLUG-250/262.6-1/2STUD  
 Active

**Web Use**  
 BURNDY Product Line

**Dimensional**

Tongue Angle	Straight
Length (in)	2.93
Tongue Type	Standard
Barrell Style	Belled
Bolt Hole Size (in)	0.52
Barrel Type	Standard
Thickness	0.18
B Length (in)	1.10
Pad Width (in)	1.29
Strip Length	1-3/16

**General**

Number of Holes	1
Product Description	Cu Comp Terminal Flex Cond, 1 Hole/W/InspWindow, 350 kcmil Code, N350 Navy, 250 kcmil Flex, 262.6 kcmil(650/#24)DLO, 600 V-35 kV, 1/2" Stud, Belled End

**Conductor(s)**

Aircraft Cable Size (Range)	N/A
Flex (Class H) Size - Range	N/A
Flex (Class I) Size - Range	250 kcmil
Copper Solid Size (Range)	N/A
DLO Size (Range)	262.6 (650/#24) DLO
Navy Cable Size (Range)	350 (91) Navy
Copper Stranded (Range)	250 kcmil
Flex (Class G) Size - Range	N/A
Flex (Class M) Size - Range	250 kcmil

**Physical**

Type of Plating	Tin - Electro Plated
Bolt Hole Size	1/2
Color Code	Red
Plated (Yes or No)	Y
Index Number	18,1025
Product Material	Copper

**Approvals / Certifications**

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175