



BURNDY Catalog Number
UPC Number
Description
Status

YA342LNN119T12E
 7818102921677
 CHAIN SAW, LPHT, 13\ " BLADE
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	5.06
Barrell Style	Chamfered
Bolt Hole Size (in)	0.52
Barrel Type	Standard
Thickness	0.22
B Length (in)	1.27
Pad Width (in)	1.19
E - in	1.75
Strip Length	1-5/16

General

Number of Holes	2
Product Description	Cu & Al Compression terminal, 500 kcmil, 600V-35Kv, 1/2 " stud, Tin plated, Brown, 20 or 299 index

Conductor(s)

Flex (Class G) Size - Range	N/A
Flex (Class H) Size - Range	N/A
Flex (Class I) Size - Range	N/A
Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	500 kcmil

Physical

Type of Plating	Tin - Electro Plated
Bolt Hole Size	1/2
Color Code	Brown
Plated (Yes or No)	Y
Index Number	20,299
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175