



BURNDY Catalog Number
UPC Number
Description
Status

YA34L2NT38FX
 7818100203711
 CULUG-350FLEX-3/8X1-NARO
 Active

Web Use
 BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	3.88
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.39
Barrel Type	Standard
Thickness	0.23
B Length (in)	1.27
Pad Width (in)	0.96
E - in	1.00
Strip Length	1-5/16
General	
Number of Holes	2
Product Description	Copper Compression Lug, 2 Hole w/ Inspection Window, 373.7 Flex, 3/8" Stud, 1" Stud Hole Spacing, Short Barrel, Tin - Electro Plated
Conductor(s)	
Flex (Class G) Size - Range	350 kcmil
Flex (Class H) Size - Range	350 kcmil
Flex (Class I) Size - Range	350 kcmil
Copper Solid Size (Range)	N/A
DLO Size (Range)	373.7 (925/#24) DLO
Copper Stranded (Range)	N/A
Physical	
Type of Plating	Tin - Electro Plated
Bolt Hole Size	3/8
Color Code	Blue
Plated (Yes or No)	Y
Index Number	19,470
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175