



BURNDY Catalog Number
UPC Number
Description
Status

YA34LB
 7818105057622
 BELLUG-350/400-5/8 STUD
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	3.56
Tongue Type	Standard
Barrell Style	Belled
Bolt Hole Size (in)	0.66
Barrel Type	Standard
Thickness	0.23
B Length (in)	1.35
Pad Width (in)	1.52
Strip Length	1-7/16

General

Number of Holes	1
Product Description	Copper Compression Lug, 1 Hole w/ Inspection Window, 350 Flex/373.7 Flex/400 Flex, 5/8" Stud, Short Barrel, Belled End, Tin Plated

Conductor(s)

Aircraft Cable Size (Range)	N/A
Flex (Class H) Size - Range	350 kcmil-400 kcmil
Flex (Class I) Size - Range	350 kcmil-400 kcmil
Copper Solid Size (Range)	N/A
DLO Size (Range)	373.7 (925/#24) DLO
Navy Cable Size (Range)	N/A
Copper Stranded (Range)	500 kcmil
Flex (Class G) Size - Range	350 kcmil-400 kcmil
Flex (Class M) Size - Range	350 kcmil

Physical

Type of Plating	Tin - Electro Plated
Bolt Hole Size	5/8
Color Code	Brown
Plated (Yes or No)	Y
Index Number	20,1027
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175