



BURNDY Catalog Number
UPC Number
Description
Status

YA40L2NNTFX
 7818102493522
 CULUG-600FLEX-NARROW TNG
 Active

Web Use
 BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	5.38
Barrell Style	Chamfered
Bolt Hole Size (in)	0.52
Barrel Type	Standard
Thickness	0.30
B Length (in)	1.42
Pad Width (in)	1.63
E - in	1.75
Strip Length	1-5/16
General	
Number of Holes	2
Product Description	Copper Compression Lug, 2 Hole w/ Inspection Window, 646 Flex, 1/2" Stud, 1-3/4" Stud Hole Spacing, Short Barrel, Tin Plated
Conductor(s)	
Flex (Class G) Size - Range	650
Flex (Class H) Size - Range	650
Flex (Class I) Size - Range	650
Copper Solid Size (Range)	N/A
DLO Size (Range)	646 (1600/#24)
Copper Stranded (Range)	650
Physical	
Type of Plating	Tin
Bolt Hole Size	1/2
Color Code	Black
Plated (Yes or No)	Y
Index Number	24
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175