



BURNDY Catalog Number
UPC Number
Description
Status

YA44L2NT38FX90
 7818100553977
 750FLX-3/8X1-NARROW-90DG
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle 90 Degree
 Length (in) 3.02
 Barrell Style Chamfered
 Bolt Hole Size (in) 0.39
 Barrel Type Standard
 Thickness 0.33
 B Length (in) 1.65
 Pad Width (in) 1.63
 E - in 1.00
 Strip Length 1-5/8

General

Number of Holes 2
 Cu Comp Terminal Flex Cond, 2 Hole/W/InspWindow, 777.7 kcmil(1925/#24)DLO, 750 kcmil FLEX, 600 V-35 kV, 3/8" Stud, 1.00" Spacing, 90 Deg Bent, Std bbl

Product Description

Conductor(s)

Flex (Class G) Size - Range 750
 Flex (Class H) Size - Range 750
 Flex (Class I) Size - Range 750
 Copper Solid Size (Range) N/A
 DLO Size (Range) 777.7 (1925/#24)
 Copper Stranded (Range) 750

Physical

Type of Plating Tin
 Bolt Hole Size 3/8
 Color Code Yellow
 Plated (Yes or No) Y
 Index Number L115
 Product Material Copper

Approvals / Certifications

UL Listed Y
 CSA Certified Y
 ROHS Compatible Compliant
 UL Recognized N
 CULUS N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175