



BURNDY Catalog Number YA44LB
UPC Number 7818105232611
Description BELLUG-750/777-5/8 STUD
Status Active

Web Use
 BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	4.50
Tongue Type	Standard
Barrell Style	Belled
Bolt Hole Size (in)	0.66
Barrel Type	Standard
Thickness	0.32
B Length (in)	1.85
Pad Width (in)	2.18
Strip Length	1-15/16
General	
Number of Holes	1
Product Description	Cu Comp Terminal Flex Cond, 1 Hole/W/InspWindow, 1000 kcmil Code CLASS G,H:750 kcmil CLASS I,K,M:650 kcmil Flex 777.7 kcmil(1325/#24)DLO, 600 V-35 kV, 5/8" Stud
Conductor(s)	
Flex (Class M) Size - Range	N/A
Aircraft Cable Size (Range)	N/A
Flex (Class H) Size - Range	750
Flex (Class I) Size - Range	650
Copper Solid Size (Range)	N/A
DLO Size (Range)	777.7 (1925/#24)
Navy Cable Size (Range)	N/A
Copper Stranded (Range)	1000
Flex (Class G) Size - Range	750
Physical	
Type of Plating	Tin - Electro Plated
Bolt Hole Size	5/8
Color Code	White
Plated (Yes or No)	Y
Index Number	27
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
 47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services
 47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175