



BURNDY Catalog Number
UPC Number
Description
Status

YA5CLB
 7818105018700
 6 CU FLEX 1-HOLE BELL 1/
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	1.73
Tongue Type	Standard
Barrell Style	Belled
Bolt Hole Size (in)	0.27
Barrel Type	Standard
Thickness	0.07
B Length (in)	0.81
Pad Width (in)	0.44
Strip Length	7/8

General

Number of Holes	1
Product Description	Cu Comp Terminal Flex Cond, 1 Hole/W/InspWindow, 5 Str Code,N30 Navy, 6 Flex, 6(61/#24)DLO, 600 V-35 kV, 1/4" Stud, Belled End

Conductor(s)

Aircraft Cable Size (Range)	N/A
Flex (Class H) Size - Range	6 AWG
Flex (Class I) Size - Range	6 AWG
Copper Solid Size (Range)	5 AWG
DLO Size (Range)	6 (61/#24) DLO
Navy Cable Size (Range)	30 (19) Navy
Copper Stranded (Range)	5 AWG
Flex (Class G) Size - Range	6 AWG
Flex (Class M) Size - Range	6 AWG

Physical

Type of Plating	Tin - Electro Plated
Bolt Hole Size	1/4
Color Code	Blue
Plated (Yes or No)	Y
Index Number	7,1014
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175

