



BURNDY Catalog Number
UPC Number
Description
Status

YAD31M10E38
 7818105496299
 300-350KCM FLEX 3/8 STUD
 Active

Web Use
 BURNDY Product Line

Dimensional

Pin Diameter	1.97
Length (in)	2.68
Outside Diameter	1.12
Thickness	0.14
B Length (in)	1.10
Pad Width (in)	1.42
Hole Size (in)	0.41
Strip Length	1-1/4

General

Product Description
 Non Insulated Brazed Barrel
 Copper Terminal, 300-350 kcmil
 Str.Cu Code & Flex (150 - 185)
 mm, 3/8", 2.74 in L, 1.46 in W,
 Tin Plated

Conductor(s)

Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	300 kcmil-350 kcmil

Physical

Type of Plating	Tin
Plated (Yes or No)	Y

Approvals / Certifications

UL Listed	N
CSA Certified	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175