



BURNDY Catalog Number
UPC Number
Description
Status

YAD33M10E38
 7818105492611
 400-450KCM FLEX 3/8 STUD
 Active

Web Use
 BURNDY Product Line

Dimensional

Pin Diameter	2.20
Length (in)	2.95
Outside Diameter	1.24
Thickness	0.16
B Length (in)	1.26
Pad Width (in)	1.50
Hole Size (in)	0.41
Strip Length	1-3/8

General

Product Description	Non Insulated Brazed Barrel Copper Terminal, 400-450 kcmil Str.Cu Code & Flex (185 - 240) mm, 3/8", 3.01 in L, 1.54 in W, Tin Plated
---------------------	--

Conductor(s)

Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	400 kcmil-450 kcmil

Physical

Type of Plating	Tin
Plated (Yes or No)	Y

Approvals / Certifications

UL Listed	N
CSA Certified	N
ROHS Compatible	Non-Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175