



BURNDY Catalog Number
UPC Number
Description
Status

YAD36M12E12
 7818105493155
 500-600KCM FLX 1/2 STUD
 Active

Web Use
 BURNDY Product Line

Dimensional

Pin Diameter	2.72
Length (in)	3.70
Outside Diameter	1.44
Thickness	0.18
B Length (in)	1.38
Pad Width (in)	1.97
Hole Size (in)	0.51
Strip Length	1-1/2

General

Product Description	Non Insulated Brazed Barrel Copper Terminal, 500-600 kcmil Str.Cu Code & Flex(240 - 300) mm, 1/2", 3.77 in L, 2.01 in W, Tin Plated
---------------------	---

Conductor(s)

Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	500 kcmil-600 kcmil

Physical

Type of Plating	Tin
Plated (Yes or No)	Y

Approvals / Certifications

UL Listed	N
CSA Certified	N
ROHS Compatible	Non-Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175