



BURNDY Catalog Number
UPC Number
Description
Status

YAD36M16E58
 7818105493222
 500-600KCM FLX 5/8 STUD
 Active

Web Use
 BURNDY Product Line

Dimensional

Pin Diameter	2.72
Length (in)	3.70
Outside Diameter	1.44
Thickness	0.18
B Length (in)	1.38
Pad Width (in)	1.97
Hole Size (in)	0.67
Strip Length	1-1/2

General

Product Description
 Non Insulated Brazed Barrel
 Copper Terminal, 500-600 kcmil
 Str.Cu Code & Flex(240 - 300)
 mm, 5/8", 3.70 in L, 1.97 in W,
 Tin Plated

Conductor(s)

Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	500 kcmil-600 kcmil

Physical

Type of Plating	Tin
Plated (Yes or No)	Y

Approvals / Certifications

UL Listed	N
CSA Certified	N
ROHS Compatible	Non-Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175