



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YAD36M20E34  
 7818105496366  
 500/600KCM FLX 3/4 STUD  
 Active

**Web Use**  
 BURNDY Product Line

**Dimensional**

Pin Diameter	2.72
Length (in)	3.70
Outside Diameter	1.44
Thickness	0.18
B Length (in)	1.38
Pad Width (in)	1.97
Hole Size (in)	0.80
Strip Length	1-1/2

**General**

**Product Description**  
 Non Insulated Brazed Barrel  
 Copper Terminal, 500-600 kcmil  
 Str.Cu Code & Flex (240 - 300)  
 mm, 3/4", 3.77 in L, 2.01 in W,  
 Tin Plated

**Conductor(s)**

Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	500 kcmil-600 kcmil

**Physical**

Type of Plating	Tin
Plated (Yes or No)	Y

**Approvals / Certifications**

UL Listed	N
CSA Certified	N
ROHS Compatible	Non-Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175