



BURNDY Catalog Number
UPC Number
Description
Status

YAE18NBOX
 7818105643011
 RING- #22-#16 AWG- NYLON
 Active

Web Use
 BURNDY Product Line

Dimensional	
Width (in)	0.07
Strip Length	3/16
Length (in)	0.92
Tongue Type	Ring
Thickness	0.03
Pad Width (in)	0.31
Electrical	
Max Voltage Rating	600
General	
Product Description	Insulug For Thin Wall Insulated Cable, 22-16 â ,Max. Insul.Dia.Accom.: .125,Color Code:Red, 8-10, .92 in L ,.31 in W, Nylon Insulated, 600 Volts Max.
Other	
Bulk Package	YAE18N
Physical	
Type of Plating	Tin
Connector Type	Terminal
Color Code	Red
Insulation Type	Nylon
Plated (Yes or No)	Y
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	Military Specified (Mil-Spec),UL486
Conductor(s)	
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	16 AWG
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175