



BURNDY Catalog Number
UPC Number
Description
Status

YAV272NFXB
 7818100766755
 CU HYLUG 3/0 1/2 STUD
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 E - in
 Strip Length

Dimensional

Straight
 5.20
 Standard
 Belled
 0.52
 Long
 0.14
 1.64
 1.03
 1.75
 1-13/16

Number of Holes

General

2
 Cu Comp Terminal Flex
 Cond(Telecom), 2
 Hole/W/O/InspWindow, 3/0
 Str,3/0(450/#24)DLO,3/0 AWG
 Code, 600 V-35 kV, 1/2" Stud,
 1.75" Spacing, Lng bbl, Belled
 End

Product Description

Conductor(s)

Aircraft Cable Size (Range)
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Navy Cable Size (Range)
 Copper Stranded (Range)
 Flex (Class G) Size - Range
 Flex (Class M) Size - Range

N/A
 3/0 AWG
 3/0 AWG
 N/A
 3/0 (450/#24) DLO
 N/A
 3/0 AWG
 3/0 AWG
 3/0 AWG

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Physical

Tin - Electro Plated
 1/2
 Orange
 Y
 14
 Copper

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

Approvals / Certifications

Y
 Y
 Compliant
 N
 N

Documentation

For further technical assistance, please contact us

47 East Industrial Park Drive
Manchester NH 03109

47 East Industrial Park Drive
Manchester NH 03109