



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YAV27L2TC38FX  
 7818100357400  
 CU HYLUG 3/0 FLEX-3/8X1  
 Active

**Web Use**  
 BURNDY Product Line

**Dimensional**

Tongue Angle	Straight
Length (in)	3.35
Tongue Type	Standard
Barrell Style	Chamfered,Skived
Bolt Hole Size (in)	0.39
Barrel Type	Standard
Thickness	0.14
B Length (in)	1.00
Pad Width (in)	1.03
E - in	1.00
Strip Length	1

**General**

Number of Holes	2
Product Description	Copper Compression Lug, 2 Hole w/ Inspection Hole, 3/0 Flex, 3/8" Stud, 1" Stud Hole Spacing, Short Barrel, Tin Plated

**Conductor(s)**

Flex (Class G) Size - Range	3/0 AWG
Flex (Class H) Size - Range	3/0 AWG
Flex (Class I) Size - Range	3/0 AWG
Copper Solid Size (Range)	N/A
DLO Size (Range)	3/0 (450/#24) DLO
Copper Stranded (Range)	3/0 AWG

**Physical**

Type of Plating	Tin
Bolt Hole Size	3/8
Color Code	Orange
Plated (Yes or No)	Y
Index Number	14
Product Material	Copper

**Approvals / Certifications**

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175