



BURNDY Catalog Number
UPC Number

YAV28LTC38FX45
7818100220611
CU HYDENT 4/0 FLEX 45 DE, 2.29
IN L
Active

Description
Status

Web Use
BURNDY Product Line

Dimensional

Tongue Angle 45 Degree
Length (in) 2.29
Tongue Type Standard
Barrell Style Chamfered
Bolt Hole Size (in) 0.39
Barrel Type Standard
Thickness 0.15
B Length (in) 1.03
Pad Width (in) 1.14
Strip Length 1-1/16

General

Number of Holes 1
Cu Comp Terminal Flex Cond, Bvl
Entry, 1 Hole/W/InspWindow, 4/0
Weld, 4/0(550/#24)DLO Flex, 4/0
AWG Code, 200 Navy, 600 V-35
kV, 3/8" Stud, 45 Deg Bent, Std
bbl

Product Description

Conductor(s)

Flex (Class G) Size - Range 4/0 AWG
Flex (Class H) Size - Range 4/0 AWG
Flex (Class I) Size - Range 4/0 AWG
Copper Solid Size (Range) N/A
DLO Size (Range) 4/0 (550/#24) DLO
Copper Stranded (Range) 4/0 AWG

Physical

Type of Plating Tin
Bolt Hole Size 3/8
Color Code Purple
Plated (Yes or No) Y
Index Number 15
Product Material Copper

Approvals / Certifications

UL Listed Y
CSA Certified Y
ROHS Compatible Compliant
UL Recognized N
CULUS N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175