



BURNDY Catalog Number
UPC Number
Description
Status

YSV1014G2
 7818100264033
 20-10 STR/SOL/FX BUTT SP
 Active

Web Use
 BURNDY Product Line

Dimensional	
Barrell Style	Chamfered
B Length (in)	0.31
General	
Product Description	Copper Reducer Butt Splice, 20-10 AWG, 0.83" Splice Length, Tin Plated
Conductor(s)	
Flex (Class H) Side A - Range	10
Aircraft Cable Size (Range)	N/A
Flex (Class M) Side B - Range	20-14
Flex (Class K) Side A - Range	10
Flex (Class G) Side B - Range	20-14
Flex (Class I) Side A - Range	10
Flex (Class H) Side B - Range	20-14
Flex (Class I) Side B - Range	20-14
Copper Solid Size (Range)	N/A
Flex (Class M) Side A - Range	10
Flex (Class G) Side A - Range	10
Flex (Class K) Side B - Range	20-14
Copper Stranded (Range)	20-10
Physical	
Type of Plating	Tin
Plated (Yes or No)	Y
Approvals / Certifications	
UL Listed	N
CSA Certified	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175